

Description

length: 0.511", grip: 0.188", thread: 8-32, close tolerance pan head bolt - cadmium plated alloy steel - tri-slot recess

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | NAS50023 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5305-01-196-3196 |



* See page 2 for technical characteristics

P/N NAS5002-3 Specifications

| | |
|-------------------------------------|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.331 Inches Nominal |
| Fastener Length: | 0.496 Inches Minimum And 0.526 Inches Maximum |
| Head Style: | Pan No. 2 |
| Head Diameter: | 0.308 Inches Minimum And 0.322 Inches Maximum |
| Head Height: | 0.088 Inches Minimum And 0.102 Inches Maximum |
| Grip Diameter: | 0.1621 Inches Minimum And 0.1627 Inches Maximum |
| Internal Drive Style: | Tri-wing Recess |
| Nominal Thread Diameter: | 0.164 Inches |
| Grip Length: | 0.170 Inches Minimum And 0.190 Inches Maximum |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Material: | Steel Comp 3140 Overall |
| Surface Treatment: | Cadmium Overall |
| Thread Series Designator: | Unjc |
| Specification/standard Data: | 80205-nas5002 Professional/industrial Association Standard |

How to Order

Order this close tolerance screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS5002-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.