

Description

length: 0.448", grip: 0.125", thread: 10-32, close tolerance pan head bolt, cadmium plated alloy steel, tri-slot recess

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | NAS50032 |
| Minimum Qty (MOQ): | 50 |
| NSN: | 5305-01-227-4608 |
| ECCN: | EAR99 |



P/N NAS5003-2 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.323 Inches Nominal |
| Fastener Length: | 0.433 Inches Minimum And 0.463 Inches Maximum |
| Head Style: | Pan No. 2 |
| Head Diameter: | 0.367 Inches Minimum And 0.373 Inches Maximum |
| Head Height: | 0.103 Inches Minimum And 0.108 Inches Maximum |
| Grip Diameter: | 0.1081 Inches Minimum And 0.1087 Inches Maximum |
| Single Shear Strength: | 95000 Pounds Per Square Inch |
| Internal Drive Style: | Tri-wing Recess |
| Nominal Thread Diameter: | 0.190 Inches |
| Grip Length: | 0.115 Inches Minimum And 0.135 Inches Maximum |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas5003 Professional/Industrial Association Standard |

How to Order

Order this close tolerance screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS5003-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.