



★ FASTENERS

Military-Fasteners.com

P/N NAS5003-2

Description

length: 0.448", grip: 0.125", thread: 10-32, close tolerance pan head bolt, cadmium plated alloy steel, tri-slot recess

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS50032
Minimum Qty (MOQ):	50
NSN:	5305-01-227-4608
ECCN:	EAR99



* See page 2 for technical characteristics

P/N NAS5003-2 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.323 Inches Nominal
Fastener Length:	0.433 Inches Minimum And 0.463 Inches Maximum
Head Style:	Pan No. 2
Head Diameter:	0.367 Inches Minimum And 0.373 Inches Maximum
Head Height:	0.103 Inches Minimum And 0.108 Inches Maximum
Grip Diameter:	0.1081 Inches Minimum And 0.1087 Inches Maximum
Single Shear Strength:	95000 Pounds Per Square Inch
Internal Drive Style:	Tri-wing Recess
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.115 Inches Minimum And 0.135 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas5003 Professional/industrial Association Standard

How to Order

Order this close tolerance screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS5003-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.