

**Description**

length: 0.573", grip: 0.250", thread: 10-32, close tolerance pan head bolt - cadmium plated alloy steel - tri-slot recess

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS50034
Minimum Qty (MOQ):	50
NSN:	5305-01-227-4611

NO IMAGE  
AVAILABLE

## P/N NAS5003-4 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.323 Inches Nominal
<b>Fastener Length:</b>	0.558 Inches Minimum And 0.588 Inches Maximum
<b>Head Style:</b>	Pan No. 2
<b>Head Diameter:</b>	0.367 Inches Minimum And 0.373 Inches Maximum
<b>Head Height:</b>	0.103 Inches Minimum And 0.108 Inches Maximum
<b>Grip Diameter:</b>	0.1885 Inches Minimum And 0.1895 Inches Maximum
<b>Single Shear Strength:</b>	95000 Pounds Per Square Inch
<b>Internal Drive Style:</b>	Tri-wing Recess
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Grip Length:</b>	0.240 Inches Minimum And 0.260 Inches Maximum
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Material:</b>	Steel Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf
<b>Specification/standard Data:</b>	80205-nas5003 Professional/Industrial Association Standard

## How to Order

Order this close tolerance screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS5003-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.