

Description

Nut Length: 3/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS500FDD10
Minimum Qty (MOQ):	5 EA
NSN:	5310-00-619-6393
Schedule B:	7616.10.1000
ECCN:	EAR99
National Motor Freight:	013540, Alum Nuts

NO IMAGE
AVAILABLE

P/N NAS500FDD10 Specifications

Mounting Hole Diameter:	0.102 Inches Minimum And 0.108 Inches Maximum
Nut Style:	Plate Nut Spacer
Nut Length:	0.735 Inches Minimum And 0.765 Inches Maximum
Thru-hole Diameter:	0.240 Inches Minimum And 0.250 Inches Maximum
Plate Thickness:	0.090 Inches Nominal
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.341 Inches Minimum And 0.347 Inches Maximum
Material:	Aluminum Alloy 2014 Overall Or Aluminum Alloy 2024 Overall Or Aluminum Alloy 7075 Overall
Material Document And Classification:	Qq-a-250/3,t6 Fed Spec 1st Material Response Overall Or Qq-a-250/5,t3 Or T42 Fed Spec 2nd Material Response Overall Or Qq-a-250/13,t6 Fed Spec 3rd Material Response Overall

How to Order

Order this nut spacer from our inventory online by visiting <https://military-fasteners.com/nuts/plain+hexagon+nuts/NAS500FDD10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.