

**Description**

Fastener Length: 1-3/16", Thread: 10-32, Thread Length: 7/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS501311                                 |
| Minimum Qty (MOQ):      | 35 EA                                     |
| NSN:                    | 5306-00-054-5744                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | 9A991                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS501-3-11 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>  | 3a   |
| <b>Thread Direction:</b>  | Right-hand                                       |
| <b>Thread Length:</b>   | 0.390 Inches Minimum And 0.437 Inches Maximum    |
| <b>Fastener Length:</b>   | 1.140 Inches Minimum And 1.187 Inches Maximum    |
| <b>Head Style:</b>  | Hexagon  |
| <b>Head Height:</b>   | 0.125 Inches Nominal                             |
| <b>Width Between Flats:</b>   | 0.365 Inches Minimum And 0.377 Inches Maximum    |
| <b>Shank Unthreaded Hole Diameter:</b>                                  | 0.070 Inches Nominal First Hole                  |
| <b>Nominal Thread Diameter:</b>   | 0.190 Inches                                     |
| <b>Grip Length:</b>   | 0.750 Inches Nominal                             |
| <b>Features Provided:</b>   | Finished Head                                    |
| <b>Thread Quantity Per Inch:</b>  | 32   |
| <b>Distance From Head Largest Bearing Surface To Shank Hole Center:</b> | 1.016 Inches Nominal First Hole                  |
| <b>Material:</b>  | Steel Comp 321 Overall Or Steel Comp 347 Overall |
| <b>Material Document And Classification:</b>                            | Qq-s-763 Fed Spec All Material Responses Overall |
| <b>Surface Treatment:</b>   | Passivate Overall                                |
| <b>Thread Series Designator:</b>  | Unf  |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS501-3-11> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.