

P/N NAS501-3-3A

Description

Fastener Length: 1/2", Thread: 10-32, Thread Length: 29/64", hexagon head, fine thread, NAS501 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS50133A

Minimum Qty (MOQ):

NSN: 5306-00-282-8542

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)







P/N NAS501-3-3A Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.375 Inches Minimum And 0.454 Inches Maximum
Fastener Length:	0.453 Inches Minimum And 0.500 Inches Maximum
Head Style:	Hexagon
Head Height:	0.109 Inches Minimum And 0.141 Inches Maximum
Width Between Flats:	0.365 Inches Minimum And 0.377 Inches Maximum
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.046 Inches Minimum And 0.078 Inches Maximum
Features Provided:	Finished Head
Thread Quantity Per Inch:	32
Material:	Steel Comp 321 Overall Or Steel Comp 347 Overall
Material Document And Classification:	Ams 5645 Assn Std 1st Material Response Overall Or Ams 5646 Assn Std 2nd Material Response Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas501 Professional/industrial Association Standard

How to Order

Order this machine bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/NAS501-3-3A and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.