

Description

Fastener Length: 13/16", Thread: 10-32, Thread Length: 29/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS50136
Minimum Qty (MOQ):	20 EA
NSN:	5306-00-576-0173
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS501-3-6 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.374 Inches Minimum And 0.453 Inches Maximum
Fastener Length:	0.765 Inches Minimum And 0.812 Inches Maximum
Head Style:	Hexagon
Head Height:	0.109 Inches Minimum And 0.141 Inches Maximum
Width Between Flats:	0.365 Inches Minimum And 0.377 Inches Maximum
Shank Unthreaded Hole Diameter:	0.070 Inches Nominal First Hole
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.359 Inches Minimum And 0.391 Inches Maximum
Features Provided:	Finished Head
Thread Quantity Per Inch:	32
Distance From Head Largest Bearing Surface To Shank Hole Center:	0.625 Inches Minimum First Hole And 0.657 Inches Maximum First Hole
Material:	Steel Comp 321 Overall Or Steel Comp 347 Overall
Material Document And Classification:	Ams 5645 Assn Std 1st Material Response Overall Or Ams 5646 Assn Std 2nd Material Response Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas501 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS501-3-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.