

P/N NAS501-3H3A

Description

Fastener Length: 15/32", Hole Diameter: 1/32", Thread: 10-32, Thread Length: 13/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS5013H3A

Minimum Qty (MOQ): 10 EA

NSN: 5306-00-818-5388

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS501-3H3A Specifications

| Thread Class: | 3a |
|---------------------------------------|---|
| Thread Direction: | Right-hand |
| Thread Length: | 0.407 Inches Minimum |
| Fastener Length: | 0.469 Inches Nominal |
| Head Style: | Hexagon |
| Head Height: | 0.125 Inches Nominal |
| Width Between Flats: | 0.375 Inches Nominal |
| Hole Diameter: | 0.046 Inches Nominal |
| Nominal Thread Diameter: | 0.190 Inches |
| Grip Length: | 0.062 Inches Nominal |
| Hole Quantity: | 1 |
| Hole Type: | Drilled |
| Features Provided: | Finished Head |
| Thread Quantity Per Inch: | 32 |
| Hole Configuration Style: | Hexagon Flats |
| Material: | Steel Comp 321 Overall |
| Material Document And Classification: | Qq-s-763 Cond A Fed Spec Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Thread Series Designator: | Unf |
| Specification/standard Data: | 80205-nas501 Professional/industrial Association Standard |

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/NAS501-3H3A and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.