

Description

Fastener Length: 1-15/16", Thread: 1/4-28, Thread Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS501417
Minimum Qty (MOQ):	5 EA
NSN:	5306-00-576-0174
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS501-4-17 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.436 Inches Minimum And 0.515 Inches Maximum
Fastener Length:	1.890 Inches Minimum And 1.937 Inches Maximum
Head Style:	Hexagon
Head Height:	0.140 Inches Minimum And 0.172 Inches Maximum
Width Between Flats:	0.428 Inches Minimum And 0.440 Inches Maximum
Shank Unthreaded Hole Diameter:	0.076 Inches Nominal First Hole
Nominal Thread Diameter:	0.250 Inches
Grip Length:	1.422 Inches Minimum And 1.454 Inches Maximum
Features Provided:	Finished Head
Thread Quantity Per Inch:	28
Distance From Head Largest Bearing Surface To Shank Hole Center:	1.734 Inches Minimum First Hole And 1.766 Inches Maximum First Hole
Material:	Steel Comp 321 Overall Or Steel Comp 347 Overall
Material Document And Classification:	Ams 5645 Assn Std 1st Material Response Overall Or Ams 5646 Assn Std 2nd Material Response Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas501 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS501-4-17> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.