

## **P/N NAS501-4H5A**

### **Description**

Fastener Length: 5/8", Hole Diameter: ", Thread: 1/4-28, Thread Length: 19/32"

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS5014H5A

Minimum Qty (MOQ): 5 EA

NSN: 5306-00-206-0944

Schedule B: 7318.15.8085

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS501-4H5A Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.594 Inches Minimum
Fastener Length:	0.656 Inches Nominal
Head Style:	Hexagon
Head Height:	0.156 Inches Nominal
Width Between Flats:	0.438 Inches Nominal
Hole Diameter:	0.062 Inches Nominal
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.062 Inches Nominal
Hole Quantity:	1
Hole Type:	Drilled
Features Provided:	Finished Head
Thread Quantity Per Inch:	28
Hole Configuration Style:	Hexagon Flats
Material:	Steel Comp 321 Overall Or Steel Comp 347 Overall
Material Document And Classification:	Qq-s-763 Fed Spec 1st Material Response Overall Or Ams 5645 Assn Std 2nd Material Response Overall Or Ams 5646 Assn Std 3rd Material Response Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas501 Professional/industrial Association Standard

## **How to Order**

Order this bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/machine+bolts/NAS501-4H5A">https://military-fasteners.com/bolts/machine+bolts/NAS501-4H5A</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.