

Description

Fastener Length: 5/8", Thread: 1/4-24, Thread Length: 35/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS50154A
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-171-9346
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS501-5-4A Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.532 Inches Minimum And 0.547 Inches Maximum
Fastener Length:	0.578 Inches Minimum And 0.625 Inches Maximum
Head Style:	Hexagon
Head Height:	0.172 Inches Minimum And 0.204 Inches Maximum
Width Between Flats:	0.490 Inches Minimum And 0.502 Inches Maximum
Nominal Thread Diameter:	0.312 Inches
Grip Length:	0.046 Inches Minimum And 0.078 Inches Maximum
Features Provided:	Finished Head
Thread Quantity Per Inch:	24
Material:	Steel Comp 321 Overall Or Steel Comp 347 Overall
Material Document And Classification:	Ams 5645 Assn Std 1st Material Response Overall Or Ams 5646 Assn Std 2nd Material Response Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas501 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS501-5-4A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.