

# **P/N NAS509-3**

## **Description**

Thread: 3-32, drilled Jamnut, NAS506 series nut

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS5093

Minimum Qty (MOQ): 10

NSN: 5310-00-616-6445

Schedule B: 7318.16.0085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









# **P/N NAS509-3 Specifications**

Thread Class:	3b
Thread Direction:	Right-hand
Nut Style:	Hexagon
Nut Height:	0.156 Inches Nominal
Drilled Hole Diameter:	0.034 Inches Minimum And 0.039 Inches Maximum
Hole Type And Quantity:	3 Drilled
Width Across Flats:	0.365 Inches Minimum And 0.377 Inches Maximum
Thread Series:	Unjf
Thread Quantity Per Inch:	32
Hardness Rating:	34.0 Rockwell C Minimum And 38.0 Rockwell C Maximum
Nominal Thread Size:	0.190 Inches
Hole Configuration Style:	Configuration B
Countersink Angle:	110.0 Degrees Nominal Nut
Bearing Surface Type:	Chamfered
Bearing Surface Finish:	125.0 Microinches
Material:	Steel Comp 4130 Overall
Material Document And Classification:	Mil-s-6758,cond F4 Mil Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas509 Professional/industrial Association Standard
Nondefinitive Spec/std Data:	2 Type

## **How to Order**

Order this plain hexagon nut from our inventory online by visiting <a href="https://military-fasteners.com/nuts/plain+hexagon+nuts/NAS509-3">https://military-fasteners.com/nuts/plain+hexagon+nuts/NAS509-3</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.