

## **P/N NAS509-8C**

### **Description**

Thread: 1/2-20, thread Size: 1/2", Nut Height: 3/8", Head Width: 3/4", drilled, NAS509 series nut

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS5098C

Minimum Qty (MOQ): 2

NSN: 5310-01-057-6724

Schedule B: 7318.16.0085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









<sup>\*</sup> See page 2 for technical characteristics

# **P/N NAS509-8C Specifications**

Thread Class:	3b
Thread Direction:	Right-hand
Nut Style:	Hexagon
Nut Height:	0.313 Inches Nominal
Drilled Hole Diameter:	0.045 Inches Minimum And 0.050 Inches Maximum
Hole Type And Quantity:	3 Drilled
Width Across Flats:	0.740 Inches Minimum And 0.752 Inches Maximum
Thread Series:	Unjf
Thread Quantity Per Inch:	20
Nominal Thread Size:	0.500 Inches
Hole Configuration Style:	Configuration B
Countersink Angle:	109.0 Degrees Minimum Both Ends And 111.0 Degrees Maximum Both Ends
Bearing Surface Type:	Chamfered
Bearing Surface Finish:	125.0 Microinches
Special Features:	150000 Psi Min Tensile Strength
Material:	Iron Alloy 660 Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas509 Professional/industrial Association Standard

## **How to Order**

Order this plain hexagon nut from our inventory online by visiting <a href="https://military-fasteners.com/nuts/plain+hexagon+nuts/NAS509-8C">https://military-fasteners.com/nuts/plain+hexagon+nuts/NAS509-8C</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.