

**Description**

NAS509L-3C Plain Hexagon Nut

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS509L3C
Minimum Qty (MOQ):	5
NSN:	5310-01-285-4359
ECCN:	EAR99
National Motor Freight:	013540, Alum Nuts

NO IMAGE  
AVAILABLE

## P/N NAS509L-3C Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Left-hand
<b>Nut Style:</b>	Hexagon
<b>Nut Height:</b>	0.146 Inches Minimum And 0.166 Inches Maximum
<b>Drilled Hole Diameter:</b>	0.034 Inches Minimum And 0.039 Inches Maximum
<b>Hole Type And Quantity:</b>	3 Drilled
<b>Width Across Flats:</b>	0.365 Inches Minimum And 0.377 Inches Maximum
<b>Thread Series:</b>	Unjf
<b>Thread Quantity Per Inch:</b>	32
<b>Nominal Thread Size:</b>	0.190 Inches
<b>Hole Configuration Style:</b>	Configuration B
<b>Countersink Angle:</b>	110.0 Degrees Nominal Both Ends
<b>Bearing Surface Type:</b>	Flat
<b>Bearing Surface Finish:</b>	125.0 Microinches
<b>Material:</b>	Iron Alloy 660 Overall
<b>Material Document And Classification:</b>	Ams 5525 Assn Std Single Material Response Overall Or Ams 5735 Assn Std Single Material Response Overall Or Ams 5737,k66286 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall
<b>Supplementary Features:</b>	150000 Psi Min Ts; U/w Nas 513,nas 559 And Nas 1193 Lock Washers On Rod End Term. To Hyd Piston
<b>Specification/standard Data:</b>	80205-nas509 Professional/Industrial Association Standard

## How to Order

Order this plain hexagon nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+hexagon+nuts/NAS509L-3C> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.