

Description

NAS509L-3C Plain Hexagon Nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS509L3C
Minimum Qty (MOQ):	5
NSN:	5310-01-285-4359
ECCN:	EAR99
National Motor Freight:	013540, Alum Nuts



* See page 2 for technical characteristics

P/N NAS509L-3C Specifications

Thread Class:	3b
Thread Direction:	Left-hand
Nut Style:	Hexagon
Nut Height:	0.146 Inches Minimum And 0.166 Inches Maximum
Drilled Hole Diameter:	0.034 Inches Minimum And 0.039 Inches Maximum
Hole Type And Quantity:	3 Drilled
Width Across Flats:	0.365 Inches Minimum And 0.377 Inches Maximum
Thread Series:	Unjf
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.190 Inches
Hole Configuration Style:	Configuration B
Countersink Angle:	110.0 Degrees Nominal Both Ends
Bearing Surface Type:	Flat
Bearing Surface Finish:	125.0 Microinches
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5525 Assn Std Single Material Response Overall Or Ams 5735 Assn Std Single Material Response Overall Or Ams 5737,k66286 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Supplementary Features:	150000 Psi Min Ts; U/w Nas 513,nas 559 And Nas 1193 Lock Washers On Rod End Term. To Hyd Piston
Specification/standard Data:	80205-nas509 Professional/industrial Association Standard

How to Order

Order this plain hexagon nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+hexagon+nuts/NAS509L-3C> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.