

P/N NAS509L12

Description

Thread Size: 3/4", Nut Height: 1/2", Head Width: 1-1/8", NAS509 series nut

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS509L12

Minimum Qty (MOQ): 5

NSN: 5310-00-725-0397

Schedule B: 7318.16.0085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)







P/N NAS509L12 Specifications

Thread Class:	3b
Thread Direction:	Left-hand
Nut Style:	Hexagon
Nut Height:	0.459 Inches Minimum And 0.479 Inches Maximum
Drilled Hole Diameter:	0.070 Inches Nominal
Hole Type And Quantity:	3 Drilled
Width Across Flats:	1.109 Inches Minimum And 1.127 Inches Maximum
Thread Series:	Unf
Thread Quantity Per Inch:	16
Hardness Rating:	34.0 Rockwell C Minimum And 38.0 Rockwell C Maximum
Nominal Thread Size:	0.750 Inches
Hole Configuration Style:	Configuration B
Countersink Angle:	109.0 Degrees Minimum Nut And 111.0 Degrees Maximum Nut
Bearing Surface Type:	Chamfered Or Washer Faced
Bearing Surface Finish:	250.0 Microinches
Material:	Steel Comp 4130 Overall
Material Document And Classification:	Mil-s-6758,cond C4 Mil Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall

How to Order

Order this plain hexagon nut from our inventory online by visiting https://military-fasteners.com/nuts/plain+hexagon+nuts/NAS509L12 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.