

Description

NAS509L3 Plain Hexagon Nut

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS509L3
Minimum Qty (MOQ):	10
NSN:	5310-01-287-6048
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



NO IMAGE
AVAILABLE

P/N NAS509L3 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Nut Style:	Hexagon
Nut Height:	0.146 Inches Minimum And 0.166 Inches Maximum
Drilled Hole Diameter:	0.034 Inches Minimum And 0.039 Inches Maximum
Hole Type And Quantity:	3 Drilled
Width Across Flats:	0.365 Inches Minimum And 0.377 Inches Maximum
Thread Series:	Unjf
Thread Quantity Per Inch:	32
Hardness Rating:	34.0 Rockwell C Minimum And 38.0 Rockwell C Maximum
Nominal Thread Size:	0.190 Inches
Hole Configuration Style:	Configuration B
Countersink Angle:	110.0 Degrees Nominal Both Ends
Bearing Surface Type:	Flat
Bearing Surface Finish:	125.0 Microinches
Material:	Steel Comp 4130 Overall
Material Document And Classification:	Mil-s-6758,cond F-4 G41300 Mil Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall And Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 2 Fed Spec All Treatment Responses Overall
Supplementary Features:	U/w Nas 513,nas 559 And Nas 1193lock Washers On Rod End Term. To Hyd Piston
Specification/standard Data:	80205-nas509 Professional/industrial Association Standard

How to Order

Order this plain hexagon nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+hexagon+nuts/NAS509L3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.