

## Description

NAS509L5C Plain Hexagon Nut

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS509L5C                                 |
| Minimum Qty (MOQ):      | 10  |
| NSN:                    | 5310-01-121-1693                          |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS509L5C Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3b   |
| <b>Thread Direction:</b>                              | Left-hand  |
| <b>Nut Style:</b>                                     | Hexagon  |
| <b>Nut Height:</b>                                    | 0.219 Inches Nominal   |
| <b>Drilled Hole Diameter:</b>                         | 0.045 Inches Minimum And 0.050 Inches Maximum  |
| <b>Hole Type And Quantity:</b>                        | 3 Drilled  |
| <b>Width Across Flats:</b>                            | 0.490 Inches Minimum And 0.502 Inches Maximum  |
| <b>Thread Series:</b>                                 | Unjf   |
| <b>Thread Quantity Per Inch:</b>                      | 24   |
| <b>Nominal Thread Size:</b>                           | 0.312 Inches   |
| <b>Hole Configuration Style:</b>                      | Configuration B  |
| <b>Countersink Angle:</b>                             | 109.0 Degrees Minimum Both Ends And 111.0 Degrees Maximum Both Ends  |
| <b>Bearing Surface Type:</b>                          | Chamfered  |
| <b>Bearing Surface Finish:</b>                        | 125.0 Microinches  |
| <b>Material:</b>                                      | Iron Alloy 660 Overall   |
| <b>Material Document And Classification:</b>          | Ams 5525 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall |
| <b>Surface Treatment:</b>                             | Passivate Overall  |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-35 Fed Spec Single Treatment Response Overall   |
| <b>Specification/standard Data:</b>                   | 80205-nas509 Professional/industrial Association Standard  |

## How to Order

Order this plain hexagon nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+hexagon+nuts/NAS509L5C> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.