

Description

Hole Diameter: 1/4", lockwasher, rod end, NAS513 series washer

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS5134
Minimum Qty (MOQ):	10
NSN:	5310-00-297-4068
Schedule B:	7318.22.0000
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



* See page 2 for technical characteristics

P/N NAS513-4 Specifications

Hole Diameter:	0.267 Inches Minimum And 0.277 Inches Maximum
Outside Diameter:	0.440 Inches Minimum And 0.460 Inches Maximum
Internal Prebent Key Width:	0.047 Inches Minimum And 0.057 Inches Maximum
Material Thickness:	0.050 Inches Nominal
Minimum Tensile Strength:	18000 Pounds Per Square Inch
Hardness Rating:	40.0 Rockwell C Minimum And 45.0 Rockwell C Maximum
Distance From Key Center To Wire Hole Center:	0.122 Inches Minimum And 0.128 Inches Maximum
Wire Hole Diameter:	0.062 Inches Nominal
Material:	Steel Comp 1095 Overall
Material Document And Classification:	Mil-s-7947,cond A Mil Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
Style Designator:	Internal Prebent Key
Specification/standard Data:	80205-nas513 Professional/industrial Association Standard

How to Order

Order this key washer from our inventory online by visiting <https://military-fasteners.com/washers/key+washers/NAS513-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.