

**Description**

Hole Diameter: 3/8", NAS513 series washer

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS5135
Minimum Qty (MOQ):	10
NSN:	5310-00-209-3573
Schedule B:	7318.22.0000
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



\* See page 2 for technical characteristics

## P/N NAS513-5 Specifications

<b>Hole Diameter:</b>	0.329 Inches Minimum And 0.339 Inches Maximum
<b>Outside Diameter:</b>	0.500 Inches Minimum And 0.520 Inches Maximum
<b>Internal Prebent Key Width:</b>	0.047 Inches Minimum And 0.057 Inches Maximum
<b>Material Thickness:</b>	0.050 Inches Nominal
<b>Minimum Tensile Strength:</b>	180000 Pounds Per Square Inch
<b>Hardness Rating:</b>	40.0 Rockwell C Minimum And 45.0 Rockwell C Maximum
<b>Distance From Key Center To Wire Hole Center:</b>	0.122 Inches Minimum And 0.128 Inches Maximum
<b>Wire Hole Diameter:</b>	0.062 Inches Nominal
<b>Material:</b>	Steel Comp 1095 Overall
<b>Material Document And Classification:</b>	Mil-s-7947 Cond 1 Mil Spec Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
<b>Style Designator:</b>	Internal Prebent Key
<b>Specification/standard Data:</b>	80205-nas513 Professional/industrial Association Standard

## How to Order

Order this key washer from our inventory online by visiting <https://military-fasteners.com/washers/key+washers/NAS513-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.