

Description

Hole Diameter: 3/8

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS5136
Minimum Qty (MOQ):	25
NSN:	5310-00-527-4509
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



* See page 2 for technical characteristics

P/N NAS513-6 Specifications

Hole Diameter:	0.388 Inches Minimum And 0.404 Inches Maximum
Outside Diameter:	0.560 Inches Minimum And 0.580 Inches Maximum
Internal Prebent Key Length:	0.031 Inches Minimum And 0.041 Inches Maximum
Internal Prebent Key Width:	0.077 Inches Minimum And 0.087 Inches Maximum
Distance From Centerline To Top Of Internal Key:	0.129 Inches Nominal
Overall Distance Including Keys:	0.738 Inches Nominal
Material Thickness:	0.050 Inches Nominal
Hardness Rating:	40.0 Rockwell C Minimum And 45.0 Rockwell C Maximum
Distance From Key Center To Wire Hole Center:	0.125 Inches Nominal
Wire Hole Diameter:	0.062 Inches Nominal
Material:	Steel Comp 1095 Overall
Material Document And Classification:	Mil-s-7947,cond A Mil Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
Style Designator:	Internal Prebent Key
Specification/standard Data:	80205-nas513 Professional/industrial Association Standard

How to Order

Order this key washer from our inventory online by visiting <https://military-fasteners.com/washers/key+washers/NAS513-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.