

**Description**

NAS513-8 Key Washer

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS5138
Minimum Qty (MOQ):	10
NSN:	5310-00-543-2426
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



NO IMAGE  
AVAILABLE

## P/N NAS513-8 Specifications

<b>Hole Diameter:</b>	0.512 Inches Minimum And 0.528 Inches Maximum
<b>Outside Diameter:</b>	0.750 Inches Minimum And 0.770 Inches Maximum
<b>Internal Prebent Key Width:</b>	0.077 Inches Minimum And 0.087 Inches Maximum
<b>Material Thickness:</b>	0.063 Inches Nominal
<b>Hardness Rating:</b>	40.0 Rockwell C Minimum And 45.0 Rockwell C Maximum
<b>Distance From Key Center To Wire Hole Center:</b>	0.153 Inches Minimum And 0.159 Inches Maximum
<b>Wire Hole Diameter:</b>	0.062 Inches Nominal
<b>Material:</b>	Steel Comp 1095 Overall
<b>Material Document And Classification:</b>	Mil-s-7947,cond A Mil Spec Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
<b>Style Designator:</b>	Internal Prebent Key
<b>Specification/standard Data:</b>	80205-nas513 Professional/industrial Association Standard

## How to Order

Order this key washer from our inventory online by visiting <https://military-fasteners.com/washers/key+washers/NAS513-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.