

**Description**

length: 11/16", thread: 10-32, full thread, philips recess, alloy steel cad ii plated

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS514P103211P
Minimum Qty (MOQ):	100
NSN:	5305-00-046-9796
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N NAS514P1032-11P Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.546 Inches Minimum And 0.608 Inches Maximum
<b>Fastener Length:</b>	0.657 Inches Minimum And 0.688 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.332 Inches Minimum And 0.385 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	125000 Pounds Per Square Inch
<b>Hardness Rating:</b>	26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Screw Material:</b>	Steel Comp 4130 Or Steel Comp 4340 Or Steel Comp 8740
<b>Screw Material Document And Classification:</b>	Mil-s-6758 Mil Spec 1st Material Response Or Mil-s-5000 Mil Spec 2nd Material Response Or Mil-s-6049 Mil Spec 3rd Material Response
<b>Screw Surface Treatment:</b>	Cadmium And Chromate
<b>Screw Surface Treatment Document And Classification:</b>	Qq-p-416, Type 2, Class 2, Fed Spec All Treatment Responses
<b>Thread Series Designator:</b>	Unjf
<b>Specification/standard Data:</b>	80205-nas514 Professional/industrial Association Standard

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS514P1032-11P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.