

**Description**

length: 1", thread: 10-32, machine screw, full thread, philips recess, alloy steel cad ii plated

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS514P103216P                            |
| Minimum Qty (MOQ):      | 100                                       |
| NSN:                    | 5305-00-964-0419                          |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



## P/N NAS514P1032-16P Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>  | 3a   |
| <b>Thread Direction:</b>                                    | Right-hand   |
| <b>Thread Length:</b>                                       | 0.827 Inches Minimum And 0.920 Inches Maximum  |
| <b>Fastener Length:</b>                                     | 0.969 Inches Minimum And 1.000 Inches Maximum  |
| <b>Head Style:</b>  | Flat Countersunk   |
| <b>Head Diameter:</b>                                       | 0.332 Inches Minimum And 0.385 Inches Maximum  |
| <b>Internal Drive Style:</b>                                | Cross Recess Type 1  |
| <b>Nominal Thread Diameter:</b>                             | 0.190 Inches   |
| <b>Thread Quantity Per Inch:</b>                            | 32   |
| <b>Minimum Tensile Strength:</b>                            | 125000 Pounds Per Square Inch  |
| <b>Countersink Angle:</b>                                   | 99.0 Degrees Minimum And 101.0 Degrees Maximum                                       |
| <b>Screw Material:</b>                                      | Steel Comp 8630 Or Steel Comp 4037   |
| <b>Screw Material Document And Classification:</b>          | Mil-s-6050 Mil Spec 1st Material Response Or Ams 6300 Assn Std 2nd Material Response |
| <b>Screw Surface Treatment:</b>                             | Cadmium And Chromate   |
| <b>Screw Surface Treatment Document And Classification:</b> | Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses                                  |
| <b>Thread Series Designator:</b>                            | Unjf   |
| <b>Specification/standard Data:</b>                         | 80205-nas514 Professional/Industrial Association Standard                            |

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS514P1032-16P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.