

**Description**

Fastener Length: 1-3/8", Thread: 10-32, Thread Length: 1-9/32

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS514P103222P
Minimum Qty (MOQ):	50
NSN:	5305-00-108-0882
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N NAS514P1032-22P Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	1.171 Inches Minimum And 1.295 Inches Maximum
<b>Fastener Length:</b>	1.313 Inches Minimum And 1.375 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.332 Inches Minimum And 0.385 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	125000 Pounds Per Square Inch
<b>Hardness Rating:</b>	26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Screw Material:</b>	Steel Comp 4037 Or Steel Comp 8630
<b>Screw Material Document And Classification:</b>	Ams 6300 Assn Std 1st Material Response Or Mil-s-6050 Mil Spec 2nd Material Response
<b>Screw Surface Treatment:</b>	Cadmium And Chromate
<b>Screw Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2 Cl 3 Fed Spec Single Treatment Response
<b>Thread Series Designator:</b>	Unjf
<b>Specification/standard Data:</b>	80205-nas514 Professional/Industrial Association Standard

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS514P1032-22P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.