

P/N NAS514P440-20P

Description

Fastener Length: 1-1/4", Thread: 4-40, Thread Length: 1-1/4

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS514P44020P

Minimum Qty (MOQ): 50

NSN: 5305-01-015-7160

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS514P440-20P Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.250 Inches Nominal
Fastener Length:	1.250 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.183 Inches Minimum And 0.225 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.112 Inches
Thread Quantity Per Inch:	40
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum
Countersink Angle:	100.0 Degrees Nominal
Screw Material:	Steel
Screw Material Document And Classification:	Mil-s-7839 Mil Spec Single Material Response
Screw Surface Treatment Document And Classification:	Qq-p-416,ty 2,clb Fed Spec All Treatment Responses
Thread Series Designator:	Unc
Specification/standard Data:	80205-nas514 Professional/industrial Association Standard

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/NAS514P440-20P and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/NAS514P440-20P and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/nashine+screws/NAS514P440-20P and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/nashine+screws/nashine