

Description


Fastener Length: 3/8", Thread: 4-40", coarse thread, flat countersunk head, NAS514 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS514P4406B
Minimum Qty (MOQ):	25
NSN:	5305-00-839-3072
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS514P440-6B Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Fastener Length:	0.375 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.183 Inches Minimum And 0.225 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.112 Inches
Thread Quantity Per Inch:	40
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum
Countersink Angle:	100.0 Degrees Nominal
Screw Material:	Steel
Screw Surface Treatment:	Cadmium And Chromate
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS514P440-6B> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.