

P/N NAS514P440-9

Description

Fastener Length: 9/16", Thread: 4-40, Thread Length: 33/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS514P4409

Minimum Qty (MOQ): 130

NSN: 5305-00-115-9358

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS514P440-9 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.436 Inches Minimum And 0.517 Inches Maximum
Fastener Length:	0.531 Inches Minimum And 0.562 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.183 Inches Minimum And 0.225 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.112 Inches
Thread Quantity Per Inch:	40
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp 4037 Or Steel Comp 8630
Screw Material Document And Classification:	Ams 6300 Assn Std 1st Material Response Or Mil-s-6050 Mil Spec 2nd Material Response
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416,ty 2 Cl 3 Fed Spec Single Treatment Response
Thread Series Designator:	Unjc
Specification/standard Data:	80205-nas514 Professional/industrial Association Standard

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/NAS514P440-9 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.