

**Description**

Fastener Length: 11/16", Thread: 6-32, Thread Length: 5/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS514P63211
Minimum Qty (MOQ):	145 EA
NSN:	5305-00-567-4991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N NAS514P632-11 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.538 Inches Minimum And 0.631 Inches Maximum
<b>Fastener Length:</b>	0.657 Inches Minimum And 0.688 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.233 Inches Minimum And 0.279 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.138 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	125000 Pounds Per Square Inch
<b>Hardness Rating:</b>	26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Screw Material:</b>	Steel Comp 4037 Or Steel Comp 8630
<b>Screw Material Document And Classification:</b>	Ams 6300 Assn Std 1st Material Response Or Mil-s-6050 Mil Spec 2nd Material Response
<b>Screw Surface Treatment:</b>	Cadmium
<b>Screw Surface Treatment Document And Classification:</b>	Qq-p-416,ty 1,cl 2 Fed Spec Single Treatment Response
<b>Thread Series Designator:</b>	Unjc
<b>Specification/standard Data:</b>	80205-nas514 Professional/Industrial Association Standard

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS514P632-11> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.