

**Description**

Fastener Length: 1-1/8", Thread: 4-40, Thread Length: 0-63/64", NAS514 series screw

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS514P63218
Minimum Qty (MOQ):	100
NSN:	5305-01-298-8336
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N NAS514P632-18 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.968 Inches Minimum And 1.080 Inches Maximum
<b>Fastener Length:</b>	1.063 Inches Minimum And 1.125 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.183 Inches Minimum And 0.225 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.112 Inches
<b>Thread Quantity Per Inch:</b>	40
<b>Minimum Tensile Strength:</b>	125000 Pounds Per Square Inch
<b>Hardness Rating:</b>	26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Screw Material:</b>	Steel Comp 8740 Or Steel Comp 8630 Or Steel Comp 8735 Or Steel Comp 4130 Or Steel Comp 4037
<b>Screw Surface Treatment:</b>	Cadmium
<b>Screw Surface Treatment Document And Classification:</b>	Qq-p-416,ty 1 Cl 2 Fed Spec Single Treatment Response
<b>Thread Series Designator:</b>	Unjc
<b>Specification/standard Data:</b>	80205-nas514 Professional/Industrial Association Standard

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS514P632-18> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.