

Description

Fastener Length: 2", Thread: 6-32, Thread Length: 2", NAS514 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS514P63232P |
| Minimum Qty (MOQ): | 25 |
| NSN: | 5305-01-004-8282 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N NAS514P632-32P Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 2.000 Inches Nominal |
| Fastener Length: | 2.000 Inches Nominal |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.233 Inches Minimum And 0.279 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.138 Inches |
| Features Provided: | Casehardened |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 125000 Pounds Per Square Inch |
| Hardness Rating: | 26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum |
| Countersink Angle: | 100.0 Degrees Nominal |
| Screw Material: | Steel |
| Screw Material Document And Classification: | Mil-s-7839 Mil Spec Single Material Response |
| Screw Surface Treatment: | Cadmium And Chromate |
| Screw Surface Treatment Document And Classification: | Qq-p-416,type 2 Class B Fed Spec Single Treatment Response |
| Thread Series Designator: | Unc |
| Specification/standard Data: | 80205-nas514 Government Standard |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS514P632-32P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.