



Military-Fasteners.com

P/N NAS514P632-32P

Description

Fastener Length: 2", Thread: 6-32, Thread Length: 2", NAS514 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS514P63232P
Minimum Qty (MOQ):	25
NSN:	5305-01-004-8282
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS514P632-32P Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	2.000 Inches Nominal
Fastener Length:	2.000 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.233 Inches Minimum And 0.279 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.138 Inches
Features Provided:	Casehardened
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum
Countersink Angle:	100.0 Degrees Nominal
Screw Material:	Steel
Screw Material Document And Classification:	Mil-s-7839 Mil Spec Single Material Response
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416,type 2 Class B Fed Spec Single Treatment Response
Thread Series Designator:	Unc
Specification/standard Data:	80205-nas514 Government Standard

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS514P632-32P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.