

**Description**

Fastener Length: 9/16", Thread: 6-32, Thread Length: 1/2"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |                                           |
|-------------------------|-------------------------------------------|
| SKU / Model:            | NAS514P6329B                              |
| Minimum Qty (MOQ):      | 30 EA                                     |
| NSN:                    | 5305-01-175-7553                          |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N NAS514P632-9B Specifications

|                                                             |                                                                                      |
|-------------------------------------------------------------|--------------------------------------------------------------------------------------|
| <b>Thread Class:</b>                                        | 3a                                                                                   |
| <b>Thread Direction:</b>                                    | Right-hand                                                                           |
| <b>Thread Length:</b>                                       | 0.412 Inches Minimum And 0.505 Inches Maximum                                        |
| <b>Fastener Length:</b>                                     | 0.531 Inches Minimum And 0.562 Inches Maximum                                        |
| <b>Head Style:</b>                                          | Flat Countersunk                                                                     |
| <b>Head Diameter:</b>                                       | 0.233 Inches Minimum And 0.279 Inches Maximum                                        |
| <b>Internal Drive Style:</b>                                | Cross Recess Type 1                                                                  |
| <b>Nominal Thread Diameter:</b>                             | 0.138 Inches                                                                         |
| <b>Thread Quantity Per Inch:</b>                            | 32                                                                                   |
| <b>Minimum Tensile Strength:</b>                            | 125000 Pounds Per Square Inch                                                        |
| <b>Hardness Rating:</b>                                     | 26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum                                  |
| <b>Countersink Angle:</b>                                   | 99.0 Degrees Minimum And 101.0 Degrees Maximum                                       |
| <b>Screw Material:</b>                                      | Steel Comp 4037 Or Steel Comp 8630                                                   |
| <b>Screw Material Document And Classification:</b>          | Ams 6300 Assn Std 1st Material Response Or Mil-s-6050 Mil Spec 2nd Material Response |
| <b>Screw Surface Treatment:</b>                             | Cadmium And Chromate                                                                 |
| <b>Screw Surface Treatment Document And Classification:</b> | Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response                                |
| <b>Color:</b>                                               | Black                                                                                |
| <b>Thread Series Designator:</b>                            | Unjc                                                                                 |
| <b>Specification/standard Data:</b>                         | 80205-nas514 Professional/industrial Association Standard                            |

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS514P632-9B> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.