

Description

Fastener Length: 0-63/64", Thread: 8-32, Thread Length: 59/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS514P83216B
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-331-7934
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS514P832-16B Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.839 Inches Minimum And 0.932 Inches Maximum
Fastener Length:	0.969 Inches Minimum And 1.000 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.232 Inches Minimum And 0.282 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp 4037 Or Steel Comp 8630
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response
Color:	Black
Thread Series Designator:	Unjc
Specification/standard Data:	80205-nas514 Professional/industrial Association Standard

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS514P832-16B> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.