

**Description**

length: 1-1/8", thread: 8-32, full thread, philips recess, alloy steel cad ii plated

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS514P83218P                             |
| Minimum Qty (MOQ):      | 50  |
| NSN:                    | 5305-01-010-3321                          |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



\* See page 2 for technical characteristics

## P/N NAS514P832-18P Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>  | 3a  |
| <b>Thread Direction:</b>                                    | Right-hand  |
| <b>Thread Length:</b>                                       | 1.063 Inches Minimum And 1.125 Inches Maximum             |
| <b>Fastener Length:</b>                                     | 1.125 Inches Nominal                                      |
| <b>Head Style:</b>  | Flat Countersunk  |
| <b>Head Diameter:</b>                                       | 0.282 Inches Minimum And 0.332 Inches Maximum             |
| <b>Internal Drive Style:</b>                                | Cross Recess Type 1                                       |
| <b>Nominal Thread Diameter:</b>                             | 0.164 Inches  |
| <b>Thread Quantity Per Inch:</b>                            | 32  |
| <b>Minimum Tensile Strength:</b>                            | 125000 Pounds Per Square Inch                             |
| <b>Hardness Rating:</b>                                     | 26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum       |
| <b>Countersink Angle:</b>                                   | 100.0 Degrees Nominal                                     |
| <b>Screw Material:</b>                                      | Steel   |
| <b>Screw Material Document And Classification:</b>          | Mil-s-7839 Mil Spec Single Material Response              |
| <b>Screw Surface Treatment:</b>                             | Cadmium And Chromate                                      |
| <b>Screw Surface Treatment Document And Classification:</b> | Qq-p-416,ty 2,clb Fed Spec All Treatment Responses        |
| <b>Thread Series Designator:</b>                            | Unc   |
| <b>Specification/standard Data:</b>                         | 80205-nas514 Professional/industrial Association Standard |

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS514P832-18P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.