

Description

Fastener Length: 1-1/4", Thread: 8-32, Thread Length: 1-1/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS514P83220
Minimum Qty (MOQ):	70 EA
NSN:	5305-01-495-0552



\* See page 2 for technical characteristics

## P/N NAS514P832-20 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	1.151 Inches Nominal
<b>Fastener Length:</b>	1.188 Inches Minimum And 1.250 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.319 Inches Minimum And 0.332 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type II
<b>Nominal Thread Diameter:</b>	0.164 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Screw Material:</b>	Steel Comp 4130 Or Steel Comp 4340 Or Steel Comp 8740
<b>Screw Material Document And Classification:</b>	Mil-s-6758 Mil Spec 1st Material Response Or Mil-s-5000 Mil Spec 2nd Material Response Or Mil-s-6049 Mil Spec 3rd Material Response
<b>Screw Surface Treatment:</b>	Cadmium
<b>Screw Surface Treatment Document And Classification:</b>	Qq-p-416,ty1cl2 Fed Spec Single Treatment Response
<b>Thread Series Designator:</b>	Unjc

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS514P832-20> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.