


Description

Fastener Length: 1-1/4", Thread: 8-32, Thread Length: 1-11/64

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS514P83220P
Minimum Qty (MOQ):	100
NSN:	5305-00-459-9548
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS514P832-20P Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.058 Inches Minimum And 1.182 Inches Maximum
Fastener Length:	1.188 Inches Minimum And 1.250 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.282 Inches Minimum And 0.332 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp 4037 Or Steel Comp 8630
Screw Material Document And Classification:	Ams 6300 Assn Std 1st Material Response Or Mil-s-6050 Mil Spec 2nd Material Response
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-b-416,ty 2,cl 3 Fed Spec All Treatment Responses
Thread Series Designator:	Unjc
Specification/standard Data:	80205-nas514 Professional/industrial Association Standard

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS514P832-20P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.