

Description

Fastener Length: 11-", Thread: 8-32, Thread Length: 10"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS514P83268 |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5305-01-357-1211 |
| National Motor Freight: | 093490, Bolt / Nut / Screw / Clips / Fastener / Etc |

NO IMAGE
AVAILABLE

P/N NAS514P832-68 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 10.870 Inches Nominal |
| Fastener Length: | 11.000 Inches Nominal |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.282 Inches Minimum And 0.332 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.164 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 125000 Pounds Per Square Inch |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Screw Material: | Steel |
| Screw Surface Treatment: | Cadmium And Chromate |
| Screw Surface Treatment Document And Classification: | Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response |
| Thread Series Designator: | Unjc |
| Specification/standard Data: | 80205-nas514 Professional/industrial Association Standard |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS514P832-68> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.