

P/N NAS514P832-68

Description

Fastener Length: 11-", Thread: 8-32, Thread Length: 10-"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS514P83268

Minimum Qty (MOQ): 1 EA

NSN: 5305-01-357-1211

National Motor Freight: 093490, Bolt / Nut / Screw / Clips / Fastener / Etc



^{*} See page 2 for technical characteristics

P/N NAS514P832-68 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	10.870 Inches Nominal
Fastener Length:	11.000 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.282 Inches Minimum And 0.332 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response
Thread Series Designator:	Unjc
Specification/standard Data:	80205-nas514 Professional/industrial Association Standard

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/NAS514P832-68 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.