

Description

Fastener Length: 4-1/2", Thread: 8-32, Thread Length: 4-3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS514P83272
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-456-0104



P/N NAS514P832-72 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	4.432 Inches Nominal
Fastener Length:	4.500 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.282 Inches Minimum And 0.332 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response
Thread Series Designator:	Unjc
Specification/standard Data:	80205-nas514 Professional/industrial Association Standard

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS514P832-72> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.