

## Description

length: 0.182", grip: 0.156", inside diameter: 0.56", drive: 1/4", NAS516 series fitting

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	NAS5161A
Minimum Qty (MOQ):	10
NSN:	4730-01-077-4893
Schedule B:	7326.90.8688
ECCN:	EAR99
National Motor Freight:	052190, Pipe,tubing,or Pipe Or Tubing Fitti



## P/N NAS516-1A Specifications

<b>Shank Length:</b>	0.131 Inches Nominal
<b>Shank Diameter:</b>	0.127 Inches Nominal
<b>Special Features:</b>	1/8 In. Flush Type Fitting W/smooth Shank,and Throat Located Ball Check Valve
<b>Height:</b>	0.182 Inches Maximum
<b>Material:</b>	Steel Body
<b>Material Document And Classification:</b>	Astm A108 B1113 Assn Std Single Material Response Body
<b>Surface Treatment:</b>	Cadmium Body
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Body
<b>Style Designator:</b>	Unthreaded
<b>Specification/standard Data:</b>	80205-nas516 Professional/industrial Association Standard

## How to Order

Order this lubrication fitting from our inventory online by visiting <https://military-fasteners.com/fittings/lubrication+ fittings/NAS516-1A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.