

Description

Unthreaded, nickel plated, NAS516 series fitting

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS5161N |
| Minimum Qty (MOQ): | 5 |
| NSN: | 4730-00-348-5328 |
| Schedule B: | 7307.19.9080 |
| ECCN: | 9A991 |
| National Motor Freight: | 052190, Pipe,tubing,or Pipe Or Tubing Fitti |



* See page 2 for technical characteristics

P/N NAS516-1N Specifications

| | |
|---|--|
| Shank Length: | 0.120 Inches Nominal |
| Shank Diameter: | 0.127 Inches Minimum And 0.129 Inches Maximum |
| Height: | 0.222 Inches Nominal |
| Material: | Steel Overall |
| Material Document And Classification: | Qq-s-630 Fed Spec 1st Material Response Overall And Qq-s-634 Fed Spec 2nd Material Response Overall Or Qq-s-637 Fed Spec 3rd Material Response Overall |
| Surface Treatment: | Nickel Overall |
| Surface Treatment Document And Classification: | Qq-n-280,class 2 Fed Spec Single Treatment Response Overall |
| Style Designator: | Unthreaded |

How to Order

Order this lubrication fitting from our inventory online by visiting <https://military-fasteners.com/fittings/lubrication+fittings/NAS516-1N> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.