

Description

Fastener Length: 1-51/64", Thread: 8-32, Thread Length: 7/16",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS517222
Minimum Qty (MOQ):	25
NSN:	5305-01-317-1510
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS517-2-22 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.376 Inches Minimum And 0.451 Inches Maximum
Fastener Length:	1.766 Inches Minimum And 1.811 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.287 Inches Minimum And 0.334 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp 8740 Or Steel Comp 8630 Or Steel Comp 8735 Or Steel Comp 4130
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response
Thread Series Designator:	Unjc
Specification/standard Data:	80205-nas517 Professional/industrial Association Standard

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS517-2-22> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.