



★ FASTENERS

Military-Fasteners.com

P/N NAS517-2-29

Description

Fastener Length: 2-15/64", Thread: 8-32, Thread Length: 7/16", NAS517 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS517229
Minimum Qty (MOQ):	5
NSN:	5305-00-811-5078
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS517-2-29 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.315 Inches Minimum And 0.452 Inches Maximum
Fastener Length:	2.204 Inches Minimum And 2.249 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.287 Inches Minimum And 0.334 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp 8630
Screw Material Document And Classification:	Mil-s-6050 Mil Spec Single Material Response Or An-s-9 Mil Std Single Material Response
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS517-2-29> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.