

Description


length: 1.156", grip: 0.750", thread: 10-32, shear, close tolerance, alloy steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS517312
Minimum Qty (MOQ):	100
NSN:	5305-00-207-1786
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS517-3-12 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.314 Inches Minimum And 0.451 Inches Maximum
Fastener Length:	1.141 Inches Minimum And 1.186 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.337 Inches Minimum And 0.387 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp 8630
Screw Material Document And Classification:	Mil-s-6050 Mil Spec Single Material Response
Screw Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response
Thread Series Designator:	Unf

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS517-3-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.