

Description


Fastener Length: 1-63/64", Thread: 10-32, Thread Length: 7/16", NAS517 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS517325
Minimum Qty (MOQ):	25
NSN:	5305-00-206-1828
Schedule B:	7318.15.6080
ECCN:	EAR99



* See page 2 for technical characteristics

P/N NAS517-3-25 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.315 Inches Minimum And 0.452 Inches Maximum
Fastener Length:	1.954 Inches Minimum And 1.999 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.337 Inches Minimum And 0.387 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp 8630
Screw Material Document And Classification:	Mil-s-6050 Mil Spec Single Material Response Or An-s-9 Mil Std Single Material Response
Screw Surface Treatment:	Cadmium
Thread Series Designator:	Unf

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS517-3-25> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.