

**Description**

Fastener Length: 2-39/64", Thread: 10-32, Thread Length: 7/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS517335   |
| Minimum Qty (MOQ):      | 10 EA   |
| NSN:                    | 5305-00-827-6545                                    |
| Schedule B:             | 7318.15.6080  |
| ECCN:                   | EAR99   |
| National Motor Freight: | 093490, Bolt / Nut / Screw / Clips / Fastener / Etc |

NO IMAGE  
AVAILABLE

## P/N NAS517-3-35 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>  | 3a  |
| <b>Thread Direction:</b>                                    | Right-hand  |
| <b>Thread Length:</b>                                       | 0.314 Inches Minimum And 0.451 Inches Maximum       |
| <b>Fastener Length:</b>                                     | 2.577 Inches Minimum And 2.622 Inches Maximum       |
| <b>Head Style:</b>  | Flat Countersunk                                    |
| <b>Head Diameter:</b>                                       | 0.337 Inches Minimum And 0.387 Inches Maximum       |
| <b>Internal Drive Style:</b>                                | Cross Recess Type 1                                 |
| <b>Nominal Thread Diameter:</b>                             | 0.190 Inches  |
| <b>Thread Quantity Per Inch:</b>                            | 32  |
| <b>Minimum Tensile Strength:</b>                            | 160000 Pounds Per Square Inch                       |
| <b>Hardness Rating:</b>                                     | 36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum |
| <b>Countersink Angle:</b>                                   | 99.0 Degrees Minimum And 101.0 Degrees Maximum      |
| <b>Screw Material:</b>                                      | Steel Comp 8630                                     |
| <b>Screw Material Document And Classification:</b>          | Mil-s-6050 Mil Spec Single Material Response        |
| <b>Screw Surface Treatment:</b>                             | Cadmium And Chromate                                |
| <b>Screw Surface Treatment Document And Classification:</b> | Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses |
| <b>Thread Series Designator:</b>                            | Unf   |

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS517-3-35> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.