

Description

Fastener Length: 2-43/64", Thread: 10-32, Thread Length: 7/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS517336
Minimum Qty (MOQ):	15 EA
NSN:	5305-00-582-9803
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS517-3-36 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.314 Inches Minimum And 0.451 Inches Maximum
Fastener Length:	2.639 Inches Minimum And 2.684 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.337 Inches Minimum And 0.387 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp 8630
Screw Material Document And Classification:	Mil-s-6050 Mil Spec Single Material Response Or An-s-9 Mil Std Single Material Response
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas517 Professional/industrial Association Standard

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS517-3-36> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.