

Description

length: 0.719", grip: 0.312", thread: 10-32 shear, close tolerance, alloy steel, NAS517 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS51735
Minimum Qty (MOQ):	100
NSN:	5305-00-639-0047
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS517-3-5 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.315 Inches Minimum And 0.452 Inches Maximum
Fastener Length:	0.704 Inches Minimum And 0.749 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.337 Inches Minimum And 0.387 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Criticality Code Justification:	Feat
Screw Material:	Steel Comp 8630
Screw Material Document And Classification:	Mil-s-6050 Mil Spec Single Material Response Or An-s-9 Mil Std Single Material Response
Screw Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response
Special Features:	Flight Safety Critical Aircraft Part
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas517 Professional/industrial Association Standard

How to Order

Order this close tolerance screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS517-3-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.